

PRECAST CONCRETE

CONCRETE MONUMENT TYPE "A"

#### **GENERAL NOTES**

DETAILS OF CONSTRUCTION, MATERIALS AND WORKMANSHIP NOT SHOWN ON THIS DRAWING SHALL CONFORM TO THE PERTINENT REQUIREMENTS OF THE STANDARD SPECIFICATIONS AND THE APPLICABLE SPECIAL PROVISIONS.

DETAILED DRAWINGS OF PROPOSED ALTERNATE DESIGNS FOR METAL MONUMENTS OR

PERMANENT MAGNETS SHALL BE INSERTED NEAR THE TOP AND BOTTOM OF ALL ALUMINUM MONUMENTS SO THE MONUMENT CAN EASILY BE DETECTED BY A METAL DETECTOR

THE CAST IRON MONUMENT COVER SHALL BE A "NON-ROCKING" TYPE. ADJUSTMENT OF THE COVER TO GRADE MAY BE ACCOMPLISHED BY THE USE OF MORTAR AND BRICK, OR BY EITHER PRECAST OR CAST-IN-PLACE REINFORCED CONCRETE GRADE RINGS.


MONUMENTS SHALL BE LOCATED AND PLACED AT THE DIRECTION OF THE ENGINEER

ALUMINUM MONUMENTS AND MONUMENT COVERS SHALL BE MADE FROM AN ALUMINUM AND

THE MONUMENT COVERS DETAILED ON THIS DRAWING ARE NOT EQUAL ALTERNATES. MONUMENT COVERS SHALL BE CAST IRON UNLESS ALUMINUM IS SPECIFIED ELSEWHERE IN THE CONTRACT

MONUMENT SHALL BE CAST-IN-PLACE CONCRETE UNLESS PRECAST CONCRETE OR ALUMINUM MONUMENTS ARE SPECIFIED IN THE CONTRACT OR PERMITTED BY THE ENGINEER.

- (1) MINIMUM LENGTH SHALL BE 4'-0" FOR MONUMENTS INSTALLED IN PAVED AREAS.
- (2) AN OFFICIAL COUNTY MONUMENT MARKER SUPPLIED BY A COUNTY MAY BE REQUIRED FOR SOME SECTION CORNERS AND WITNESS MONUMENTS INSTEAD OF THIS WISDOT MARKER.





# LID TO BE ATTACHED TO FRAME WITH STAINLESS STEEL FLAT HEAD SCREWS MACHINE FACED P.C. CONCRETE PVC PIPE TO FIT PAVEMENT OR MAX. 1 FOOT TYPE "C" OR "D" MONUMENTS

#### **SECTION B-B SECTION A-A ALUMINUM MONUMENT COVER**

(APPROXIMATE WEIGHT 2 LBS) (FOR CONCRETE PAVEMENT ONLY)

# **CONCRETE MONUMENTS** LID TO BE BOLTED AND TYPE A P.C. CONCRETE **PAVEMENT** CRUSHED AGGREGATE BASE COURSE PRE-CAST CONCRETE RINGS OR CAST-IN-PLACE CONCRETE VLAWFUL 12" FOUNDATION BACKFILL COMPACTED IN TWO 6" LAYERS 6" LAYERS OF COMPACTED FOUNDATION BACKFILL FOR

**PRECAST** 

<sup>2</sup> WIS DOT MONUMENT **MARKER LOGO** 

FOR TYPES "A", "C" & "D"

- 3 ¼" DIA.

**CAST-IN-PLACE** 

**CAST IRON MONUMENT COVER** 

(APPROXIMATE WEIGHT 95 LBS)

**ALUMINUM MONUMENTS** (INCLUDES MARKER)

ASPHALTIC

CONCRETE

4 NO 4 BARS FOR CAST-

12" FOUNDATION BACKFILL

COMPACTED IN TWO 6" LAYERS

IN-PLACE CONCRETE

UNDISTURBED EARTH FOR

CRUSHED AGGREGATE

> LANDMARK REFERENCE **MONUMENTS AND COVERS**

STATE OF WISCONSIN DEPARTMENT OF TRANSPORTATION

APPROVED March 2018 DATE /S/ Raymond A. Kumapayii CHIEF SURVEYING AND MAPPII ENGINEER

0

#### References:

FDM 9-5-1 FDM 9-25-1 FDM 9-25-10

### Bid items associated with this drawing:

ITEM NUMBER	<u>DESCRIPTION</u>	<u>UNIT</u>
621.0100	Landmark Reference Monuments	EACH
621.1100	Landmark Reference Monuments and Cast Iron Covers	EACH
621.1200	Landmark Reference Monuments and Aluminum Covers	EACH

### Standardized Special Provisions associated with this drawing:

STSP NUMBER TITLE

NONE

# Other SDDs associated with this drawing:

NONE

#### **Design Notes:**

A landmark "Reference" monument may also be used as the official monument marking a land boundary or a highway reference line such as a section corner.

# **Contact Person:**

Chief, Surveying and Mapping Section (608)246-3835